

22R08AZ Receiver

UL Class 1 Division 1, Groups B, C, and D

- 4 form-A Control Relays
- 4 form-C Control Relays
- 120 VAC Power Supply
- NEMA 7/8 Enclosure
- 9 ft. Remote Antenna Kit



RF Characteristics

RF unit.....	Microprocessor controlled PLL synthesizer with up to 85 different channels
Frequency Range.....	902-928 Megahertz (MHz)
Channel Spacing.....	300 Kilohertz(KHz)
Modulation.....	Packet Mode, Digital Frequency, Modulation(FM) based on Manchester code
Receiver Type.....	Dual Conversion FM
FCC ID #.....	EGT810RX
Industry Canada Certification #.....	249 710 2624A
Sensitivity.....	1 µV usable
IF Bandwidth.....	180 KHz
Response Time.....	60 Milliseconds
Update Rate.....	16 packets per second command, 4 packets per second idle
Range.....	300- ft. obstructed view, 1000-ft. line of sight (unobstructed)
RF approvals.....	License-free in North America
Antenna.....	3" tuned element

Safety and Operational Characteristics

Relays.....	4 form-C control relays and 4 form-A control relays
Output Contacts.....	5 Amps @ 230 VAC
Addressing Safety.....	16-bit, 65,535 unique addresses with 85 channels providing over 5 million variations
Safety Decoding.....	16-bit Cyclic Redundancy Codes (CRC) check
Safety Stop.....	Over-riding Stop command with safety relay
Start-Up Safety.....	Start inhibited if controls pressed before start
Status Indications.....	Full function diagnostics LED indicators for Power, Signal and Output
Power Requirements.....	120 VAC power supply
Maximum Current Drain.....	0.12 Amps @ 115 VAC

Environmental Characteristics

Temperature Range.....	-20° to +160° F (-29° to +71° C)
Humidity Range.....	0-97% maximum non-condensing
UL Rating.....	UL Class 1 Division 1, Groups B, C, and D
Environmental Rating.....	NEMA 7/8

Physical Characteristics

Connector.....	Terminal Strip Connection
Antenna.....	Case Mounted or remote
Housing Material.....	Metal (optional fiberglass and stainless steel)
Weight.....	8.125 lbs. (3.69 kg)
Dimensions.....	12.32" x 12.32" x 8.10" (31.3 cm x 31.3 cm x 20.6 cm)