

LHD

Cattron™



PORTABLE RADIO REMOTE CONTROL FOR LOAD-HAUL-DUMP VEHICLES

MCU

- Designed to be mounted on high vibration mining machinery
- Systems also available with custom PWM (pulse width modulation) configurations
- Multiple watchdog circuits
- 2-digit system status display (acts as a central test point)
- Automatic Safety Override (ASO) output monitoring
- Addressing and time sharing to permit multiple units to share each radio frequency
- Extremely high message security
- Extensive self diagnostics
- BCH data error
- Auto select 12-24 VDC input power supply
- Compatible with Autodig™*
- Optional joystick controller/transmitter styles with fiberglass or aluminum dustproof, waterproof impact housings

JOYSTICK OCU

- Quick response
- Accurate, secure radio control
- CE, FCC and DOC approved (contact factory for other approvals)
- Microprocessor control
- Extensive self-diagnostics
- Long battery operating life (NiCad rechargeable or alkaline)
- Dustproof, waterproof impact housings

MODELS

MCU

AT16LHD incorporates 16 independent functions, plus run on/off outputs

AT32LHD offers up to 5 digital proportional functions, plus up to 7 independent, as well as run

OCU

C01LHD, fiberglass enclosure

P06C, aluminium enclosure

APPLICATIONS

CONTROLLERS (C01LHD, P06C)

Dimensions (H x W x D) & weight	C01LHD	P06C
	15 x 35.5 x 9.5 cm (6 x 14 x 3 ¾ inches)	15 x 34.3 x 17 cm (5.9 x 13.5 x 6.7 inches)
	approx. 5.5 kg (12 lbs.), including battery	approx. 4.2 kg (9 lbs.), including battery

Operating band UHF 450–470 MHz (others available on request)

Standard RF power output 20–40 mW output power (higher power available on request)

Spurious and harmonic emissions More than 33 db below carrier

Antenna Internal

Modulation digital frequency Shift Keying (FSK)

Enclosure	C01LHD	P06C
	Fiberglass NEMA (4x)	Aluminum

RECEIVER/DECODERS (AT16LHD AND AT32LHD)

Dimensions (H x W x D)	Approx. 30.5 x 25.5 x 15 cm (12 x 10 x 6 inches)
-------------------------------	-----------------------------------------------------

Interface type	AT16LHD	AT32LHD
	Mechanical relays normally open contacts 8A @250VAC or 5A @ 30VDC maximum	Proportional, current control with DDEC throttle control interface. Optional custom PWM configurations available

Environment Operate from -30° to +60 °C (-25° to 140° F), with non-condensing relative humidity from 0 to 95 %.

Output termination	AT16LHD	AT32LHD
	16 pin connector (military specification)	24 pin connector (military specification), optional connector configurations available

Enclosure NEMA 4 steel (optional stainless steel or fiberglass)
Individual EMI-shielded compartments for subchassis receiver, decoder and power supply. Entire sub-chassis mounts on inside door of NEMA 4 enclosure. Relays not in sub-chassis.

Power requirements	12-24 VDC	± 10% @ less than 2 amps, ± 20% @ less than 1 amp (12 VDC)
	24 VDC	2 pin power connector, for both AT16LHD and AT32 LHD.

*Autodig™ is a trademark of Elphinstone™.

USA: +1.234.806.0018
Systems-US-Sales@lairdtech.com

Europe: +49.2151.4795.0
Systems-EU-Sales@lairdtech.com

Asia: +86.21.3120.0188
Systems-CN-Sales@lairdtech.com

Latin America: +55.19.3518.7030
Systems-BR-Sales@lairdtech.com

www.lairdtech.com

LHD_DS_EN_201810

Any information furnished by Laird Limited, its subsidiary companies and its agents (hereafter, "Laird") is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird disclaims liability for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect at the time of sale. A current copy of the Laird Terms and Conditions will be furnished upon request. This document is © Copyright 2018, Laird, all rights reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks of Laird. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.