

CommandPro™

REMTRON™ HANDHELD TRANSMITTERS



HANDHELD TRANSMITTERS DESIGNED TO PERFORM AND SURVIVE IN TOUGH ENVIRONMENTS SUCH AS STEEL AND MANUFACTURING PLANTS

HIGHLIGHTS

- 3 different sizes with up to 23 control functions
- Rugged case, made from advanced composites, holds up to tough industrial environments

FEATURES

- Low power consumption for long battery life – typically one to two months with AA batteries
- Internal antenna prevents breakage
- LED provides transmitter and battery status
- Includes leather holster for added protection
- Long-life rocker switches with positive tactile feel
- IP 66 design on the T10, T14 and T18

MODELS

T10 / 6" SIZE

- Compact configuration that provides up to 10 control functions
- Versatile and economical control solution

T14/18 / 8" SIZE

- Expands to 14 control functions
- Optimal for use with heavy duty gloves


T20/23 / 12" SIZE

- Expands to 23 control functions
- Powerful control system allows direct selection of speeds for accurate control

APPLICATIONS

Remtron™ solutions are specifically designed to handle critical industrial and construction tasks using the unlicensed 900 MHz frequency band.

- Overhead Cranes
- Heavy Machinery
- Ship Loaders
- Metal Fabrication
- Amusement Parks
- Lifting Equipment





TECHNICAL DATA AND SPECIFICATIONS

ELECTRONIC DATA

Commands	T10 – 8 functions T14 – 12 functions T18 – 18 functions T20 – 20 functions T23 – 22 functions
Digital Circuitry	Microprocessor based
System Address	16-bit, 65,535 unique addresses
Energy-Saving Mode	Variable transmission rate for fast response to change
Battery	2 AA Alkaline batteries
Battery Life	>130 hours typical

MECHANICAL DATA

Weight	T10 - 0.50 lbs. T14/18 - 0.75lbs. T20/23 - 1.25 lbs.
Dimensions L x W x H	T10 - 6"x 3"x 1" Z14/18 - 8"x 3"x 1" T20/23 - 12"x 4" x 1"
Housing	High-impact, fiber-reinforced nylon T10/14/18 IP66 T20/23 IP54
Operating Temperature	-29° to +71° C (-20° to +160° F)
Vibration and Shock	Very rugged design for tough industrial use

RF

Frequency Range	902-928 MHz
Transmitter Output Power	1mW license exempt
Modulation	Packet Mode, FM
RF Channel Spacing	300 KHz
Antenna	Internal

OPERATION AND INDICATION

Actuators Layout	Ergonomic and protected switch elements
Control elements	Various single/dual-speed rocker switches, auxiliary push buttons, start, stop

ACCESSORIES

Batteries	2 standard AA
Labeling	Custom options

North America: +1.234.806.0018 | Sales.US@Cattron.com
Europe: +49.2151.4795.0 | Sales.EU@Cattron.com
UK: +44.1932.238121 | Sales.UK@Cattron.com
South America: +55.19.3518.7030 | Sales.BR@Cattron.com
Asia: Sales.CN@Cattron.com

cattron.com

COMMANDPRO_EN_201902

Any information furnished by Cattron™ and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Cattron products rests with the end user since Cattron and its agents cannot be aware of all potential uses. Cattron makes no warranties as to non-infringement nor as to the fitness, merchantability, or sustainability of any Cattron products for any specific or general uses. Cattron Holdings, Inc., or any of its affiliates or agents shall not be liable for incidental or consequential damages of any kind. All Cattron products are sold pursuant to the Terms and Conditions of Sale, a copy of which will be furnished upon request. When used as a tradename herein, Cattron means Cattron Holdings, Inc. or one or more subsidiaries of Cattron Holdings, Inc. Cattron™, corresponding logos, and other marks are trademarks or registered trademarks of Cattron Holdings, Inc. Other marks may be the property of third parties. Nothing herein provides a license under any Cattron or any third party intellectual property right.

