

SCU32

CATTRONCONTROL™



FIXED STATION DEVICE FOR SECURE POINT TO POINT TRANSMISSION

HIGHLIGHTS

- Transmits up to 32 digital commands plus 2 safety stop commands
- System configuration via a secure RFID Transkey for simple deployment and spares implementation
- Customer-specific layout with a wide range of control elements
- Approvals and frequencies for worldwide deployment

FEATURES

- Galvanic isolation of inputs
- Internal, isolated power supply for opto-isolated inputs
- Industrial AC power supply and DC options available
- LEDs for status and feedback (optional)
- Custom faceplate available
- High safety class through redundant hardware and firmware architecture

APPLICATIONS


The SCU32 is a robust, industrial grade control unit that provides 32 opto-isolated inputs for secure wireless point to point, or point to multi-point transfer of control commands.

- Machine control
- Conveyor Control
- Secure point to point
- Amusement Parks

COMPLIANCE

Safety

- EN 60204-32
- EN ISO 13557
- EN ISO 13849 PLd
- CE Compliant





TECHNICAL DATA AND SPECIFICATIONS

ELECTRONIC DATA

Commands	32 digital inputs
Digital Circuitry	Dual-processor Technology
System Addresses	24 bits =16 million addresses

MECHANICAL DATA

Weight	Approx. 1.8 kg
Dimensions L x W x H	235 x 170 x 105mm (9.25"x 6.7" x 4.2")
Housing	Polymeric, standard color gray
Interface connection	IP65, suitable for outdoor use
Operating temperature	2 cable glands optional: Han24/32/64
Storage temperature	-20° to +60° C (-4° to +140° F)
	-40 to +70° C (-40 to 158° F)

ELECTRICAL DATA

Power supply	48, 115, 230 V, 50-60 Hz
Nominal voltage	12V (24V optional)
Power consumption	Max. 10 VA
Opto-Couplers	12V dc input
	Internal 12 V for opto-couplers available
Frequency range	406-419 MHz 433-434 MHz 447-473 MHz 869 MHz 902-927 MHz Other frequencies possible
Regulatory	Licensed and unlicensed bands available
Transmitter output power	10-500 mW
RF Security	Black Channel
RF channel spacing	12.5 kHz; 25 kHz and others
Antenna	External

INDICATION

Operation indication	2 LEDs for status and diagnostics
----------------------	-----------------------------------

North America: +1.234.806.0018 | Sales.US@Cattron.com
Europe: +49.2151.4795.0 | Sales.EU@Cattron.com
UK: +44.1932.238121 | Sales.UK@Cattron.com
South America: +55.19.3518.7030 | Sales.BR@Cattron.com
Asia: Sales.CN@Cattron.com

cattron.com

SCU32_EN_201902

Any information furnished by Cattron™ and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Cattron products rests with the end user since Cattron and its agents cannot be aware of all potential uses. Cattron makes no warranties as to non-infringement nor as to the fitness, merchantability, or sustainability of any Cattron products for any specific or general uses. Cattron Holdings, Inc., or any of its affiliates or agents shall not be liable for incidental or consequential damages of any kind. All Cattron products are sold pursuant to the Terms and Conditions of Sale, a copy of which will be furnished upon request. When used as a tradename herein, Cattron means Cattron Holdings, Inc. or one or more subsidiaries of Cattron Holdings, Inc. Cattron™, corresponding logos, and other marks are trademarks or registered trademarks of Cattron Holdings, Inc. Other marks may be the property of third parties. Nothing herein provides a license under any Cattron or any third party intellectual property right.

