

# Bi-Directional Amplifier

SIAMnet™



## UNDERGROUND MINING COMMUNICATION SYSTEMS

### HIGHLIGHTS


- 800 MHz LMR band, supports multiple wireless voice and data channels concurrently
- CATV Cable Modem band, supports DOCSIS high-speed Ethernet and WIFI networks
- Diagnostic system, supports remote monitoring and configuration

### FEATURES

- Excellent 800MHz signals propagation, covers long distances
- Supports analog and/or digital, conventional and/or trunking two-way radio systems
- Uses low-cost CATV cable and accessories available worldwide
- Power from the CATV coaxial cable eliminates costly AC power outlet installations and allows for an efficient battery backup system
- Diagnostic capability enables troubleshooting and remote configuration without going onsite

### APPLICATIONS

- Combining two-Way voice and mobile data communication technologies with high speed data networks make the SIAMnet the perfect communication system for underground mines.
- Wireless vehicular communication systems for dispatch, monitoring and production control
- Underground mines (non-coal)
- Railway tunnels





## TECHNICAL DATA AND SPECIFICATIONS

800 MHz amplifier	Downlink	Uplink	Remarks
800MHz SMR Band	851-870 MHz	806-825 MHz	
Flatness	0.5 dB	0.5 dB	
Gain	34 dB or better	34 dB or better	
Maximum Input Power (port P1)	0 dBm	0 dBm	
Input Attenuator Option	10 dB	10 dB	Separately activated, locally or remotely
Maximum Power, Single Carrier	+33 dBm	+30 dBm	± 1 dB
Manual Gain Control	0–34 dB	0–34 dB	Independently, in 1 dB steps
Noise Figure	6 dB	6 dB	
1 dB Compression Point	+33 dBm	+26 dBm	± 2 dB
Channel Separation	>40 dB	>40 dB	
Port Impedance	75 ohm	75 ohm	CATV compatible KS connection
Test Points	F female	F female	20 dB attenuation

Cable Modem Amplifier	Downstream	Upstream	Remarks
Frequency Bands	150-190MHz	5-90 MHz	DOCSIS & EuroDOCSIS
Flatness	0.5dB	0.5 dB	
Gain	0–25 dB	0–25 dB	
Equalizer Adjustment	0.5–2 dB	0–8 dB	
Maximum Power, Single Carrier	+ 54 dBmv	+54 dBmv	0 dBm=48.75 dBmv

Electrical & Mechanical		
Uplink Port (P1), Downlink Port (p2)	5-870 MHz	Bi-directional port, 800 MHz and cable modem
RF and AC Power	45-60 Vac 10 A	
AC Power Source	P1 or P2	Select port from which AC power is present
AC Power Pass Through P1-P2	On/Off	Locally or remotely activated relay contact
AC Power Breaker	10 Amps	Resettable locally or remotely
Internal Diagnostic LEDs	5 total	P1 AC power, P2 AC power, PA power OK, AC Trip, F1 fuse blown
Operating Ambient Temperature	-20 to +50C	The ambient temperature may be less once the amplifier has started and reached its operating temperature
Housing	NEMA 4	Aluminum casting, used as heat sink, IP67, RF sealed.
Overall Dimensions	10.5 X 7.5 X 4.5"	
Weight	3 kg	
Connectors	KS female	P1, P2

North America: +1.234.806.0018 | Sales.US@Cattron.com

Europe: +49.2151.4795.0 | Sales.EU@Cattron.com

UK: +44.1932.238121 | Sales.UK@Cattron.com

South America: +55.19.3518.7030 | Sales.BR@Cattron.com

Asia: Sales.CN@Cattron.com

[cattron.com](http://cattron.com)

9A06-S-BDA-A001



# CATTRON™

Any information furnished by Cattron™ and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Cattron products rests with the end user since Cattron and its agents cannot be aware of all potential uses. Cattron makes no warranties as to non-infringement nor as to the fitness, merchantability, or sustainability of any Cattron products for any specific or general uses. Cattron Holdings, Inc., or any of its affiliates or agents shall not be liable for incidental or consequential damages of any kind. All Cattron products are sold pursuant to the Terms and Conditions of Sale, a copy of which will be furnished upon request. When used as a tradename herein, Cattron means Cattron Holdings, Inc. or one or more subsidiaries of Cattron Holdings, Inc. Cattron™, corresponding logos, and other marks are trademarks or registered trademarks of Cattron Holdings, Inc. Other marks may be the property of third parties. Nothing herein provides a license under any Cattron or any third party intellectual property right.