

MP96RCL

CATTRON™ FOR RAIL

TOP OF THE LINE LOCOMOTIVE REMOTE CONTROL SYSTEM FOR THROTTLE/BRAKE OPERATION

HIGHLIGHTS

- Multiple systems can operate on one frequency
 - System performs in-depth self-test on power up and constantly monitors key parameters during operation
 - Accessible components allow for ease of maintenance
-

FEATURES

- Up to 48 inputs and 96 outputs allow for complete customization
 - Responds rapidly to operator commands
 - Individually fused and isolated outputs
 - Single-point status display shows normal and fault conditions
 - Throttle/brake control with Proportional Independent Brake Control and Monitoring
 - Wheel slip control
-

OPTIONS

- Can be configured with different controller models
 - Digital talkback- two-way digital communication between the Operator Control Unit (OCU) and the Locomotive Control Unit (LCU) through text display and function LED's on the OCU
 - Pitch & Catch
 - Proportional train brake control and monitoring
 - Remote mounting option for system display increases flexibility of installation location
 - The MP96RCL has an integrated ability to store an internal archive record, configure system operating parameters and support live monitoring of system IO. This is all capable through the maintenance terminal link – either through a direct connect serial connection, or through a 4G wireless modem connection. Options include required hardware and PC Applications.
-

APPLICATIONS

Offering the safety and dependability required for operating in railroad environments, the MP96RCL enables one operator on the ground to effectively control switching operations and train movements. The system enables the operator to input all commands from a safe distance while having greater visibility along the length of the train.





TECHNICAL DATA AND SPECIFICATIONS

FEATURE	SPECIFICATION
Enclosure	NEMA 4 enclosure; dust, oil & watertight
Environmental	Approx. -4 to +140 °F (-20 to +60 °C), RH 0 to 95%, non-condensing
Control Voltage Range	36 VDC or 72 VDC fused @ 5 amps
Power Requirements	36 VDC or 72 VDC @ less than 5 amps
Internal Archive Record Size	32 MB
Compliance	Can be configured to comply to 49 CFR § 229.15

North America: +1.234.806.0018 | Sales.US@Cattron.com
Europe: +49.2151.4795.0 | Sales.EU@Cattron.com
UK: +44.1932.238121 | Sales.UK@Cattron.com
South America: +55.19.3518.7030 | Sales.BR@Cattron.com
Asia: Sales.CN@Cattron.com

cattron.com

9A06-MP96RCL-A001-EN, Rev. 1.0

Any information furnished by Cattron™ and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Cattron products rests with the end user since Cattron and its agents cannot be aware of all potential uses. Cattron makes no warranties as to non-infringement nor as to the fitness, merchantability, or sustainability of any Cattron products for any specific or general uses. Cattron Holdings, Inc., or any of its affiliates or agents shall not be liable for incidental or consequential damages of any kind. All Cattron products are sold pursuant to the Terms and Conditions of Sale, a copy of which will be furnished upon request. When used as a tradename herein, Cattron means Cattron Holdings, Inc. or one or more subsidiaries of Cattron Holdings, Inc. Cattron™, corresponding logos, and other marks are trademarks or registered trademarks of Cattron Holdings, Inc. Other marks may be the property of third parties. Nothing herein provides a license under any Cattron or any third party intellectual property right.

