

Vehicle Communication System

SIAMnet™



DIGITAL ETHERNET DATA COMMUNICATION BETWEEN UNDERGROUND MOBILE MACHINERY AND SURFACE COMPUTER NETWORKS

HIGHLIGHTS

- Our cast aluminum enclosure protects your equipment in the harshest mining environment
- Up to 220 vehicles can be monitored on a single network with the master/slave capacity
- The web-based configuration center uses a standard web browser to configure the system whether locally or remotely

FEATURES


- 800 MHz LMR band propagates better than VHF or UHF in confined spaces and the 806–869 MHz bandwidth supports multiple mobile channels/ multiple networks
- Frequency and space diversity ensure uninterrupted data transmissions in mine tunnels
- The large buffer memory means you'll never lose data even when the communication is interrupted
- Dual radio channels provide 100% coverage in a tunnel
- Linux operating system-based
- TCP/IP protocols with Ethernet and Serial ports ensures compatibility with every data communication technologies keeps software packages up to date
- Tri-color status LEDs facilitates troubleshooting the system

MODELS

1005	VCS Master Radio modem, 800MHz
1006	VCS Slave Radio modem, 800MHz, Fixed, one radio
1007	VCS Slave Radio modem, 800MHz, Mobile, one radio
1007E	VCS Slave Radio modem, 800MHz, Mobile, one radio, Ethernet only
1008	VCS Slave Radio modem, 800MHz, Mobile, dual radios
1008E	VCS Slave Radio modem, 800MHz, Mobile, dual radios, Ethernet only


APPLICATIONS

- Daily Operations
Help workers communicate flawlessly with each other's and boost productivity
- Two-Way Voice
Discover conventional two-way voice communication to link underground and surface workers
- Dispatch
Get support for loaders and trucks at automated loading and dumping points
- Data Networks
Explore LAN: an application that extends into underground mines to provide critical communication for underground operators
- WIFI
Enable people or machinery to communicate over networks without the need for a wired connection





Vehicular Communication System



TECHNICAL DATA AND SPECIFICATIONS

ELECTRICAL DATA

Electrical power	9–36 VDC
RF power	1 watt
RF sensitivity	-85 dBm
Operating band	800 MHz LMR
Channel bandwidth	150 KHz
Termination	TNC female
Over the air data rates	90 kbps

MECHANICAL DATA

Dimensions	9" x 7.75" x 3.75" (228 x 197 x 95 mm)
Environmental	IP66/67
Weight	5.5lbs / 2.5 kg

North America: +1.234.806.0018 | Sales.US@Cattron.com

Europe: +49.2151.4795.0 | Sales.EU@Cattron.com

UK: +44.1932.238121 | Sales.UK@Cattron.com

South America: +55.19.3518.7030 | Sales.BR@Cattron.com

Asia: Sales.CN@Cattron.com

cattron.com

9A06-S-VCS-A001



Any information furnished by Cattron™ and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Cattron products rests with the end user since Cattron and its agents cannot be aware of all potential uses. Cattron makes no warranties as to non-infringement nor as to the fitness, merchantability, or sustainability of any Cattron products for any specific or general uses. Cattron Holdings, Inc., or any of its affiliates or agents shall not be liable for incidental or consequential damages of any kind. All Cattron products are sold pursuant to the Terms and Conditions of Sale, a copy of which will be furnished upon request. When used as a trademark herein, Cattron means Cattron Holdings, Inc. or one or more subsidiaries of Cattron Holdings, Inc. Cattron™, corresponding logos, and other marks are trademarks or registered trademarks of Cattron Holdings, Inc. Other marks may be the property of third parties. Nothing herein provides a license under any Cattron or any third party intellectual property right.