



724-399-3051

Air-Eagle Receivers Product Guide



Click on the links to view detailed product information.



Single Relay				
		SR Plus 600 foot range 2.4 GHz	XLT 2500 foot range 900 MHz	XLT Plus 5000 foot range 900 MHz
	100-250VAC	38-20100-AC	441-20100-AC	na
	9-36VDC	38-20100-DC	441-20100-DC	na
Responds to user-selectable button on transmitter	100-250VAC	38-20100-X-AC	441-20100-X-AC	na
	9-36VDC	38-20100-X-DC	441-20100-X-DC	na



Three Relays				
		SR Plus 600 foot range 2.4 GHz	XLT 2500 foot range 900 MHz	XLT Plus 5000 foot range 900 MHz
	100-250VAC	na	na	461-5000-AC
	9-36VDC	na	na	461-5000-DC



Four Relays				
		SR Plus 600 foot range 2.4 GHz	XLT 2500 foot range 900 MHz	XLT Plus 5000 foot range 900 MHz
	100-250VAC	38-2000-AC	441-8000-AC	461-8000-AC
	9-36VDC	38-2000-DC	441-8000-DC	461-8000-DC
	10-24VDC	38UL-2000-DC	44UL-2000-DC	na
Sends confirmation of relay activation to transmitter	100-250VAC	38-2000-VBR-AC	441-8000-VBR-AC	461-8000-VBR-AC
	9-36VDC	38-2000-VBR-DC	441-8000-VBR-DC	461-8000-VBR-DC



Eight Relays				
		SR Plus 600 foot range 2.4 GHz	XLT 2500 foot range 900 MHz	XLT Plus 5000 foot range 900 MHz
	100-250VAC	38-20800-AC	441-20800-AC	461-20800-AC
	9-36VDC	38-20800-DC	441-20800-DC	461-20800-DC
	10-24VDC	38UL-20800-DC	44UL-20800-DC	na



Sixteen Relays				
		SR Plus 600 foot range 2.4 GHz	XLT 2500 foot range 900 MHz	XLT Plus 5000 foot range 900 MHz
	100-250VAC	38-21600-AC	441-21600-AC	461-21600-AC
	9-36VDC	38-21600-DC	441-21600-DC	461-21600-DC



Specialty				
		SR Plus 600 foot range 2.4 GHz	XLT Up to 2 miles 900 MHz	XLT Plus 5000 foot range 900 MHz
Three High Current Relay, Momentary or Toggle	100-250VAC	38HC-2000	441HC-8000	na
	9-36VDC	38HC-2000-DC	441HC-8000-DC	na

Visit cattron.com to view the portfolio.