



PRODUCT COMPARISON



250



240



250G1H



240G1H

| | | | | |
|--|--|--|--|--|
| Digital hour meter | ● | ● | ● | ● |
| Single gauge | | | ● | ● |
| Two to seven gauges | ● | ● | | |
| Key switch & starter output (5% duty cycle) | 75A for 1 sec/18A continuous@ 12V; 25k mechanical cycles | 75A for 1 sec/18A continuous@ 12V; 25k mechanical cycles | 75A for 1 sec/18A continuous@ 12V; 25k mechanical cycles | 50A for 1 sec/12A continuous@ 12V; 25k mechanical cycles |
| Tachometer frequency input (if option wiring kit used) | Alternator, proximity switch or magnetic pickup | | Alternator, proximity switch or magnetic pickup | |
| First Fault Diagnostics (FFD) | ● | ● | ● | ● |
| Operating temp -40°F to 122°F (-40°C to 50°C) | ● | ● | ● | ● |
| System voltage (10-28 VDC) | ● | ● | ● | ● |
| Reverse polarity protection | ● | ● | ● | ● |
| Starter relay (suggested) | ● | ● | ● | ● |
| Run/Stop solenoid (15 A max) | ● | ● | ● | ● |
| 15 (F) / accessory (15 A max, fused) | ● | ● | ● | ● |
| Battery charge indication / alternator excitation | ● | ● | ● | ● |
| Alarm output | 750 mA | | 750 mA | |
| Configurable features | ● | | ● | |
| Temperature switch input | ● | ● | ● | ● |
| Oil pressure switch input | ● | ● | ● | ● |
| Additional inputs | 3 | 2 | 3 | 2 |
| Positive preheat | ● | | ● | |
| Preheat options (input or output) | positive or ground | ground | positive or ground | ground |
| Mini Aluflex™ | | | ● | ● |
| Standard Aluflex™ | ● | ● | ● | ● |
| Two year limited warranty | ● | ● | ● | ● |

Learn more about LOFA panels at cattron.com

